



6911 Marlin Circle, La Palma, CA 90623  
(714) 523-8700, Fax (714) 523-3220

## Suzuki VZR1800 M109 465 Series Single Shock Supplement

Please read these instructions completely before starting!

1. Shouldered sleeves with O-rings should already be installed in the shock eyes. If not, insert sleeves with O-rings in both top and bottom eyes (see figure 1). Note: The widest sleeves go in the bottom eye.




figure 1

2. Mount the shock, referencing your authorized shop manual, noting the following important details: Make sure pressure valve is towards the front wheel and facing up. The rebound adjuster end of the shock be mounted towards the rear wheel and facing down. Tighten shock bolts to the proper torque specifications (refer to authorized shop manual).

**Caution:** The installed spring length must never be set shorter than 6.20" for 465-1165 and 5.80" for 465-1166 or shock damage may occur.

<http://www.progressivesuspension.com>



6911 Marlin Circle, La Palma, CA 90623  
(714) 523-8700, Fax (714) 523-3220

## Suzuki VZR1800 M109 465 Series Single Shock Supplement

Please read these instructions completely before starting!

1. Shouldered sleeves with O-rings should already be installed in the shock eyes. If not, insert sleeves with O-rings in both top and bottom eyes (see figure 1). Note: The widest sleeves go in the bottom eye.




figure 1

2. Mount the shock, referencing your authorized shop manual, noting the following important details: Make sure pressure valve is towards the front wheel and facing up. The rebound adjuster end of the shock be mounted towards the rear wheel and facing down. Tighten shock bolts to the proper torque specifications (refer to authorized shop manual).

**Caution:** The installed spring length must never be set shorter than 6.20" for 465-1165 and 5.80" for 465-1166 or shock damage may occur.

<http://www.progressivesuspension.com>